



Sperrkantscheibe

ABMESSUNGEN - mittlere Form "M"

Für Schrauben von	d min.-max.	D min.-max.	s min.-max.	ca. Gewicht kg/1000 St.	h min.-max.	Anzahl Sperrkanten	Verpackungseinheit
4	4.10-4.40	9.80-10.20	0.95-1.05	0.470	1.25-1.50	16	1.000
5	5.10-5.40	11.80-12.20	1.16-1.24	0.790	1.55-1.90	20	1.000
6	6.10-6.40	13.77-14.20	1.36-1.44	1.240	1.85-2.20	20	1.000
8	8.20-8.56	17.68-18.20	1.36-1.44	2.030	1.95-2.40	24	1.000
10	10.20-10.56	21.73-22.25	1.55-1.65	3.490	2.25-2.75	24	1.000
12	12.40-12.83	26.73-27.25	1.75-1.85	6.010	2.60-3.10	24	500
14	14.40-14.83	29.63-30.25	2.34-2.46	9.370	3.20-3.70	24	250
16	16.40-16.83	31.88-32.50	2.44-2.56	10.650	3.45-3.95	28	250
18	18.50-19.25	34.38-35.00	2.94-3.06	15.200	4.00-4.50	28	250
20	21.00-21.75	39.38-40.00	2.94-3.06	20.400	4.20-4.70	30	100
22	23.00-23.75	44.38-45.00	3.44-3.56	30.400	4.80-5.30	30	100
24	25.00-25.75	49.38-50.00	3.44-3.56	38.200	5.10-5.60	32	100
27	28.00-28.85	59.26-60.00	3.91-4.09	69.000	6.10-6.60	36	100
30	31.00-31.85	69.26-70.00	4.41-4.59	109.000	7.30-7.80	36	50

ABMESSUNGEN - schmale Form "S"

4	4.10-4.40	7.80-8.20	0.95-1.05	0.270	1.15-1.40	16	1.000
5	5.10-5.40	9.80-10.20	0.95-1.05	0.400	1.25-1.50	20	1.000
6	6.10-6.40	11.77-12.20	1.16-1.24	0.707	1.55-1.85	20	1.000
8	8.20-8.56	15.77-16.20	1.36-1.44	1.500	1.90-2.40	24	1.000
10	10.20-10.56	19.73-20.25	1.55-1.65	2.640	2.10-2.60	24	1.000
12	12.40-12.83	23.73-24.25	1.55-1.65	3.870	2.20-2.70	24	500


ABMESSUNGEN - breite Form "B"

6	6.10-6.40	17.68-18.20	1.36-1.44	2.470	2.15-2.55	20	1.000
8	8.20-8.56	21.73-22.25	1.84-1.96	4.880	2.60-3.00	24	1.000
10	10.20-10.56	26.73-27.25	2.34-2.46	9.200	3.20-3.70	24	1.000
12	12.40-12.83	31.68-32.30	2.74-2.86	14.620	4.10-4.60	24	500

ABMESSUNGEN - für Zylinderschrauben Form "Z"

6	6.10-6.40	9.54-9.90	1.36-1.44	0.500	1.50-1.80	20	1.000
8	8.20-8.56	12.34-12.70	1.36-1.44	0.780	1.55-1.85	24	1.000
10	10.20-10.56	15.74-16.10	1.55-1.65	1.420	1.85-2.20	24	1.000
12	12.40-12.83	17.78-18.30	1.75-1.85	1.780	2.05-2.45	24	500
14	14.40-14.83	20.88-21.40	2.34-2.46	3.190	2.70-3.10	24	250
16	16.40-16.83	24.08-24.60	2.44-2.56	4.400	2.90-3.30	28	250

Ausführungen: roh gefettet
Zink-Lamellen Beschichtung
andere Oberflächenausführungen auf Anfrage



Sperrkantscheibe gezahnt

ABMESSUNGEN - gezahnte Form "K"

Für Schrauben von	d min.-max.	D min.-max.	s min.-max.	ca. Gewicht kg/1000 St.	h min.-max.	Anzahl Sperrkanten	Verpackungseinheit
4	4.10-4.40	7.80-8.20	0.95-1.05	0.250	1.20-1.35	16	1.000
5	5.10-5.40	9.80-10.20	0.95-1.05	0.410	1.25-1.50	20	1.000
6	6.10-6.40	11.80-12.20	1.16-1.24	0.710	1.50-1.80	20	1.000
8	8.20-8.56	15.80-16.20	1.36-1.44	1.500	1.90-2.40	24	1.000
10	10.20-10.56	19.75-20.25	1.55-1.65	2.680	2.15-2.60	24	1.000
12	12.40-12.83	23.75-24.25	1.55-1.65	3.850	2.15-2.70	24	500

Ausführungen: roh gefettet
Zink-Lamellen Beschichtung
andere Oberflächenausführungen auf Anfrage





Sperrkantscheibe

ABMESSUNGEN - mittlere Form "M"

Für Schrauben von	d min.-max.	D min.-max.	s min.-max.	ca. Gewicht kg/1000 St.	h min.-max.	Anzahl Sperrkanten	Verpackungseinheit
4	4.10-4.40	9.80-10.20	0.95-1.05	0.470	1.25-1.50	16	1.000
5	5.10-5.40	11.80-12.20	1.16-1.24	0.790	1.55-1.90	20	1.000
6	6.10-6.40	13.77-14.20	1.36-1.44	1.240	1.85-2.20	20	1.000
8	8.20-8.56	17.68-18.20	1.36-1.44	2.030	1.95-2.40	24	1.000
10	10.20-10.56	21.73-22.25	1.55-1.65	3.490	2.25-2.75	24	1.000
12	12.40-12.83	26.73-27.25	1.75-1.85	6.010	2.60-3.10	24	500
14	14.40-14.83	29.63-30.25	2.34-2.46	9.370	3.20-3.70	24	250
16	16.40-16.83	31.88-32.50	2.44-2.56	10.650	3.45-3.95	28	250
18	18.50-19.25	34.38-35.00	2.94-3.06	15.200	4.00-4.50	28	250
20	21.00-21.75	39.38-40.00	2.94-3.06	20.400	4.20-4.70	30	100
22	23.00-23.75	44.38-45.00	3.44-3.56	30.400	4.80-5.30	30	100
24	25.00-25.75	49.38-50.00	3.44-3.56	38.200	5.10-5.60	32	100
27	28.00-28.85	59.26-60.00	3.91-4.09	69.000	6.10-6.60	36	100
30	31.00-31.85	69.26-70.00	4.41-4.59	109.000	7.30-7.80	36	50

ABMESSUNGEN - schmale Form "S"

4	4.10-4.40	7.80-8.20	0.95-1.05	0.270	1.15-1.40	16	1.000
5	5.10-5.40	9.80-10.20	0.95-1.05	0.400	1.25-1.50	20	1.000
6	6.10-6.40	11.77-12.20	1.16-1.24	0.707	1.55-1.85	20	1.000
8	8.20-8.56	15.77-16.20	1.36-1.44	1.500	1.90-2.40	24	1.000
10	10.20-10.56	19.73-20.25	1.55-1.65	2.640	2.10-2.60	24	1.000
12	12.40-12.83	23.73-24.25	1.55-1.65	3.870	2.20-2.70	24	500


ABMESSUNGEN - breite Form "B"

6	6.10-6.40	17.68-18.20	1.36-1.44	2.470	2.15-2.55	20	1.000
8	8.20-8.56	21.73-22.25	1.84-1.96	4.880	2.60-3.00	24	1.000
10	10.20-10.56	26.73-27.25	2.34-2.46	9.200	3.20-3.70	24	1.000
12	12.40-12.83	31.68-32.30	2.74-2.86	14.620	4.10-4.60	24	500

ABMESSUNGEN - für Zylinderschrauben Form "Z"

6	6.10-6.40	9.54-9.90	1.36-1.44	0.500	1.50-1.80	20	1.000
8	8.20-8.56	12.34-12.70	1.36-1.44	0.780	1.55-1.85	24	1.000
10	10.20-10.56	15.74-16.10	1.55-1.65	1.420	1.85-2.20	24	1.000
12	12.40-12.83	17.78-18.30	1.75-1.85	1.780	2.05-2.45	24	500
14	14.40-14.83	20.88-21.40	2.34-2.46	3.190	2.70-3.10	24	250
16	16.40-16.83	24.08-24.60	2.44-2.56	4.400	2.90-3.30	28	250

Werkstoff: Rost- und säurebeständiger Stahl, Werkstoff A4



Sperrkantscheibe gezahnt

ABMESSUNGEN - gezahnte Form "K"

Für Schrauben von	d min.-max.	D min.-max.	s min.-max.	ca. Gewicht kg/1000 St.	h min.-max.	Anzahl Sperrkanten	Verpackungseinheit
4	4.10-4.40	7.80-8.20	0.95-1.05	0.250	1.20-1.35	16	1.000
5	5.10-5.40	9.80-10.20	0.95-1.05	0.410	1.25-1.50	20	1.000
6	6.10-6.40	11.80-12.20	1.16-1.24	0.710	1.50-1.80	20	1.000
8	8.20-8.56	15.80-16.20	1.36-1.44	1.500	1.90-2.40	24	1.000
10	10.20-10.56	19.75-20.25	1.55-1.65	2.680	2.15-2.60	24	1.000
12	12.40-12.83	23.75-24.25	1.55-1.65	3.850	2.15-2.70	24	500

Werkstoff: Rost- und säurebeständiger Stahl, Werkstoff A4

