



Zahnscheiben

ABMESSUNGEN

für Schrauben von	d min.-max.	D min.-max.	s	Anzahl Zähne	kg/1.000 Stück	Verpackungseinheit
M 2	2,20-2,34	4,20-4,50	0,30	6	0,020	5.000
M 2,3	2,50-2,64	4,70-5,00	0,30	6	0,025	5.000
M 2,5	2,70-2,84	5,20-5,50	0,40	6	0,037	5.000
M 3	3,20-3,38	5,70-6,00	0,40	6	0,042	1.000
M 3,5	3,70-3,88	6,64-7,00	0,50	6	0,077	1.000
M 4	4,30-4,48	7,64-8,00	0,50	8	0,095	1.000
M 5	5,10-5,28	8,64-9,00	0,60	8	0,180	1.000
M 5	5,30-5,48	9,64-10,00	0,60	8	0,180	1.000
M 6	6,40-6,62	10,57-11,00	0,70	8	0,217	1.000
M 7	7,40-7,62	12,07-12,50	0,80	8	0,330	1.000
M 8	8,20-8,42	13,57-14,00	0,80	8	0,421	1.000
M 8	8,40-8,62	14,57-15,00	0,80	8	0,450	1.000
M 10	10,50-10,77	17,57-18,00	0,90	9	0,800	1.000
M 12	13,00-13,27	19,98-20,50	1,00	10	1,000	1.000
M 14	15,00-15,27	23,48-24,00	1,00	10	1,600	1.000
M 16	17,00-17,27	25,48-26,00	1,20	12	2,000	500
M 18	19,00-19,33	29,48-30,00	1,40	12	3,500	500
M 20	21,00-21,33	32,38-33,00	1,40	12	3,800	200
M 22	23,00-23,33	35,38-36,00	1,50	14	5,000	100
M 24	25,00-25,33	37,38-38,00	1,50	14	6,000	100
M 27	28,00-28,33	43,38-44,00	1,60	14	8,000	100
M 30	31,00-31,39	47,38-48,00	1,60	14	9,000	100

Härte: 350-425 HV

roh gefettet

galvanisch verzinkt

andere Oberflächenausführungen auf Anfrage