



ASME B 18 21 1 1999 REGULAR

CARBON STEEL

STAINLESS STEEL AISI 304 / 316

Split Lock Washers

DIMENSIONS in mm

for screws of	d min.-max.	D max.	b min.-max.	s min.-max.	h min.-max	kg/1.000 pcs	Packing Unit
No. 2	2,24-2,39	4,37	0,90-0,99	0,56-0,64	1,11-1,31	0,050	1.000
No. 3	2,57-2,71	4,95	1,02-1,17	0,70-0,84	1,42-1,68	0,065	1.000
No. 4	2,90-3,05	5,30	1,02-1,17	0,70-0,84	1,42-1,68	0,070	1.000
No. 5	3,23-3,38	6,00	1,19-1,29	0,86-1,00	1,71-2,01	0,110	1.000
No. 6	3,58-3,76	6,34	1,19-1,29	0,86-1,00	1,71-2,01	0,130	1.000
No. 8	4,24-4,42	7,44	1,40-1,51	1,10-1,24	2,16-2,25	0,220	1.000
No. 10	4,90-5,08	8,48	1,57-1,70	1,28-1,42	2,48-2,92	0,305	1.000
No. 12	5,59-5,77	9,58	1,78-1,93	1,52-1,67	3,00-3,50	0,490	1.000
1/4"	6,40-6,60	12,36	2,77-2,88	1,72-1,96	3,38-3,98	1,030	1.000
5/16"	7,98-8,18	14,80	3,17-3,31	2,15-2,39	4,17-4,91	1,730	1.000
3/8"	9,58-9,78	17,26	3,58-3,74	2,59-2,83	4,97-5,87	2,770	1.000
7/16"	11,18-11,43	19,71	3,96-4,14	2,99-3,23	5,71-6,73	4,410	500
1/2"	12,75-13,00	22,06	4,34-4,53	3,41-3,65	6,48-7,64	5,800	500
9/16"	14,33-14,58	24,52	4,78-4,97	3,84-4,08	7,27-8,57	8,060	500
5/8"	15,95-16,28	27,23	5,16-5,49	4,24-4,48	8,00-9,44	10,600	250
3/4"	19,13-19,43	32,11	6,94-6,34	5,11-5,35	9,60-11,32	18,100	250
7/8"	22,30-22,70	37,06	6,76-7,38	5,95-6,45	11,40-13,40	29,400	100
1"	25,48-26,01	42,06	7,54-8,29	6,80-7,30	12,95-15,25	42,600	100
1 1/8"	28,68-29,28	46,91	8,34-9,09	7,60-8,10	14,50-16,90	58,500	50
1 1/4"	31,85-32,51	51,71	9,12-9,87	8,42-8,92	15,99-18,69	77,120	50
1 1/2"	38,20-38,96	61,44	10,72-11,47	10,12-10,62	19,19-22,29	132,000	50

Material

STAINLESS STEEL AISI 304 / AISI 316 Hardness: 345 - 420 Hv

CARBON STEEL Hardness: 372 - 458 Hv

other raw material on enquiry