



Federringe

ABMESSUNGEN

für Schrauben von	d min.-max.	D max.	b min.-max.	s min.-max.	h min.-max	kg/1.000 Stück	Verpackungs- einheit
1/8"	3,20-3,50	6,30	1,20-1,40	0,70-0,90	1,60-1,90	0,120	1.000
5/32"	4,10-4,40	7,60	1,40-1,60	0,80-1,00	1,80-2,10	0,190	1.000
3/16"	4,90-5,30	9,10	1,70-1,90	1,10-1,30	2,40-2,80	0,380	1.000
1/4"	6,50-6,90	12,20	2,35-2,65	1,50-1,70	3,20-3,80	0,900	1.000
5/16"	8,10-8,50	14,80	2,85-3,15	1,90-2,10	4,00-4,70	1,670	1.000
3/8"	9,80-10,30	17,70	3,30-3,70	2,05-2,35	4,40-5,20	2,560	1.000
7/16"	11,20-11,70	19,10	3,30-3,70	2,05-2,35	4,40-5,20	2,850	1.000
1/2"	13,20-13,70	22,10	3,80-4,20	2,35-2,65	5,00-5,90	4,320	500
9/16"	14,30-14,80	24,20	4,30-4,70	2,85-3,15	6,00-7,10	6,330	500
5/8"	15,90-16,70	27,10	4,80-5,20	3,30-3,70	7,00-8,30	9,280	250
3/4"	19,30-20,30	32,70	5,80-6,20	3,80-4,20	8,00-9,40	15,390	100
7/8"	22,50-23,50	35,90	5,80-6,20	3,80-4,20	8,00-9,40	17,600	100
1"	25,80-26,80	41,30	6,75-7,25	4,80-5,20	10,00-11,80	28,920	100

Härte: 430-510 HV
roh gefettet
galvanisch verzinkt, mechanisch verzinkt
andere Oberflächenausführungen auf Anfrage