ASME B18.2.1 1 REGULAR

CARBON STEEL

STAINLESS STEEL AISI 301 / 316

Split Lock Washers



DIMENSIONS in inch

for screws of	d min.-max.	D max.	b min.-max.	s min.		kg/1.000 pcs	Packing Unit
No. 2	0,088-0,094	0,172	0,024-0,035	0,020		0,050	1.000
No. 3	0,101-0,107	0,195	0,028-0,040	0,025		0,065	1.000
No. 4	0,114-0,120	0,209	0,028-0,040	0,025		0,070	1.000
No. 5	0,127-0,133	0,236	0,033-0,047	0,031		0,110	1.000
No. 6	0,141-1,148	0,250	0,033-0,047	0,031		0,130	1.000
No. 8	0,167-0,174	0,293	0,038-0,055	0,040		0,220	1.000
No. 10	0,193-0,200	0,334	0,043-0,062	0,047		0,305	1.000
No. 12	0,220-0,227	0,377	0,049-0,070	0,056		0,490	1.000
1/4"	0,252-0,260	0,487	0,076-0,109	0,062		1,030	1.000
5/16"	0,314-0,322	0,583	0,087-0,125	0,078		1,730	1.000
3/8"	0,377-0,385	0,680	0,099-0,141	0,094		2,770	1.000
7/16"	0,440-0,450	0,776	0,109-0,156	0,109		4,410	500
1/2"	0,502-0,512	0,869	0,120-0,171	0,125		5,800	500
9/16"	0,564-0,574	0,965	0,132-0,188	0,141		8,060	500
5/8"	0,628-0,641	1,073	0,142-0,203	0,156		10,600	250
3/4"	0,753-0,766	1,265	0,164-0,234	0,188		18,100	250
7/8"	0,878-0,894	1,459	0,186-0,266	0,219		29,400	100
1"	1,003-1,024	1,656	0,208-0,297	0,250		42,600	100
1 1/8"	1,129-1,153	1,847	0,230-0,328	0,281		58,500	50
1 1/4"	1,254-1,280	2,036	0,251-0,359	0,312		77,120	50
1 1/2"	1,504-1,534	2,419	0,295-0,422	0,375		132,000	50

Material

STAINLESS STEEL AISI 301 / AISI 316 Hardness: 345 - 420 Hv

CARBON STEEL Hardness: 372 - 458 Hv

COATINGS: oiled, electro zinc plated whitre and yellow, mechanical zinc plated white ans yellow, zinc-flake hot dip galvanised (dimensions might be out of range, due to thickness of the coating)

other raw material and coatings on enquiry