



Sperrkant Spring Washer Sem

Dimensions and Specifications

| For screws of | d min.-max. | D max. | s min.-max. | b min. - max | h min.-max. | Weight kg/1000 pcs. | Packaging |
|---------------|-------------|--------|-------------|--------------|-------------|---------------------|-----------|
| 4 | 3,60-3,75 | 6,95 | 0,70-0,90 | 1,40-1,60 | 1,20-1,40 | 0,15 | 100.000 |
| 5 | 4,55-4,75 | 8,55 | 0,90-1,10 | 1,70-1,90 | 1,50-1,70 | 0,30 | 50.000 |
| 6 | 5,50-5,70 | 11,00 | 1,20-1,40 | 2,35-2,65 | 2,00-2,20 | 0,64 | 25.000 |
| 8 | 7,40-7,65 | 13,95 | 1,50-1,70 | 2,85-3,15 | 2,45-2,75 | 1,23 | 10.000 |
| 10 | 9,30-9,55 | 16,95 | 1,70-1,90 | 3,30-3,70 | 2,85-3,15 | 2,00 | 5.000 |
| 12 | 11,0-11,3 | 19,70 | 1,95-2,25 | 3,80-4,20 | 3,35-3,65 | 3,10 | 2.500 |

Special features: grid shaped surface ("Sperrkanten")
 wire profile alternately bend
 apex of the dome between 135°-150°
 5-times deflected

technical specifications according to DIN 6905

Finishings: oiled
 other raw material and coatings on inquiry

