


**Sperrkant washer**

BN 208010

Dimensions - medium form "M"							Tightening Torque (Nm)	Packaging
For screws of	d min.-max.	D min.-max.	s = b min.-max.	h min.-max.	Weight kg/1000 pcs.	Number of Sperrkanten	0.18 $\mu$	Packaging
4	4.10-4.40	9.80-10.20	0.95-1.05	1.25-1.50	0.470	16	2,8	1.000
5	5.10-5.40	11.80-12.20	1.16-1.24	1.55-1.90	0.790	20	5,3	1.000
6	6.10-6.40	13.77-14.20	1.36-1.44	1.85-2.20	1.240	20	9,1	1.000
8	8.20-8.56	17.68-18.20	1.36-1.44	1.95-2.40	2.030	24	21,8	1.000
10	10.20-10.56	21.73-22.25	1.55-1.65	2.25-2.75	3.490	24	44,0	1.000
12	12.40-12.83	26.73-27.25	1.75-1.85	2.60-3.10	6.010	24	75,0	500
14	14.40-14.83	29.63-30.25	2.34-2.46	3.20-3.70	9.370	24	120,0	250
16	16.40-16.83	31.88-32.50	2.44-2.56	3.45-3.95	10.650	28	180,0	250
18	18.50-19.25	34.38-35.00	2.94-3.06	4.00-4.50	15.200	28	-	250
20	21.00-21.75	39.38-40.00	2.94-3.06	4.20-4.70	20.400	30	-	100
22	23.00-23.75	44.38-45.00	3.44-3.56	4.80-5.30	30.400	30	-	100
24	25.00-25.75	49.38-50.00	3.44-3.56	5.10-5.60	38.200	32	-	1.120,0
27	28.00-28.85	59.26-60.00	3.91-4.09	6.10-6.60	69.000	36	-	100
30	31.00-31.85	69.26-70.00	4.41-4.59	7.30-7.80	109.000	36	-	50

Dimensions - small form "S"							Tightening Torque (Nm)	Packaging
For Screws of	d min.-max.	D min.-max.	s = b min.-max.	h min.-max.	Weight kg/1000 pcs.	Number of Sperrkanten	0.18 $\mu$	Packaging
4	4.10-4.40	7.80-8.20	0.95-1.05	1.15-1.40	0.270	16	2,8	1.000
5	5.10-5.40	9.80-10.20	0.95-1.05	1.25-1.50	0.400	20	5,3	1.000
6	6.10-6.40	11.77-12.20	1.16-1.24	1.55-1.85	0.707	20	9,1	1.000
8	8.20-8.56	15.77-16.20	1.36-1.44	1.90-2.40	1.500	24	21,8	1.000
10	10.20-10.56	19.73-20.25	1.55-1.65	2.10-2.60	2.640	24	44,0	1.000
12	12.40-12.83	23.73-24.25	1.55-1.65	2.20-2.70	3.870	24	75,0	500

Dimensions - large form "B"							Tightening Torque (Nm)	Packaging
For Screws of	d min.-max.	D min.-max.	s = b min.-max.	h min.-max.	Weight kg/1000 pcs.	Number of Sperrkanten	0.18 $\mu$	Packaging
6	6.10-6.40	17.68-18.20	1.36-1.44	2.15-2.55	2.470	20	9,1	1.000
8	8.20-8.56	21.73-22.25	1.84-1.96	2.60-3.00	4.880	24	21,8	1.000
10	10.20-10.56	26.73-27.25	2.34-2.46	3.20-3.70	9.200	24	44,0	1.000
12	12.40-12.83	31.68-32.30	2.74-2.86	4.10-4.60	14.620	24	75,0	500

Dimensions - head cap screw form "Z"							Tightening Torque (Nm)	Packaging
For Screws of	d min.-max.	D min.-max.	s = b min.-max.	h min.-max.	Weight kg/1000 pcs.	Number of Sperrkanten	0.18 $\mu$	Packaging
6	6.10-6.40	9.54-9.90	1.36-1.44	1.50-1.80	0.409	20	9,1	1.000
8	8.20-8.56	12.34-12.70	1.36-1.44	1.55-1.85	0.670	24	21,8	1.000
10	10.20-10.56	15.74-16.10	1.55-1.65	1.85-2.20	1.299	24	44,0	1.000
12	12.40-12.83	17.78-18.30	1.75-1.85	2.05-2.45	1.650	24	75,0	500
14	14.40-14.83	20.88-21.40	2.34-2.46	2.70-3.10	3.000	24	120,0	250
16	16.40-16.83	24.08-24.60	2.44-2.56	2.90-3.30	4.400	28	180,0	250

The tightening torques listed below are only valid as an indication - referring to VDI 2230.

Raw material: stainless and acid-proofed steel, material A4