

**ASME B 18 21 1 2009 REGULAR**

CARBON STEEL

STAINLESS STEEL AISI 304 / 316

Split Lock Washers**DIMENSIONS in mm**

for screws of	d max.	d min.	D max.	Thickness min.	Width min.	kg/1.000 pcs	Packing Unit
No. 2	2,39	2,24	4,37	0,51	0,89	0,050	1.000
No. 3	2,72	2,57	4,95	0,64	1,02	0,065	1.000
No. 4	3,05	2,90	5,31	0,64	1,02	0,070	1.000
No. 5	3,38	3,23	5,99	0,79	1,19	0,110	1.000
No. 6	3,76	3,58	6,35	0,79	1,19	0,130	1.000
No. 8	4,42	4,24	7,44	1,02	1,40	0,220	1.000
No. 10	5,08	4,90	8,48	1,19	1,57	0,305	1.000
No. 12	5,77	5,59	9,58	1,42	1,78	0,490	1.000
1/4"	6,60	6,40	12,37	1,57	2,77	1,030	1.000
5/16"	8,18	7,98	14,81	1,98	3,18	1,730	1.000
3/8"	9,78	9,58	17,27	2,39	3,58	2,770	1.000
7/16"	11,43	11,18	19,71	2,77	3,96	4,410	500
1/2"	13,00	12,75	22,07	3,18	4,34	5,800	500
9/16"	14,58	14,33	24,51	3,58	4,78	8,060	500
5/8"	16,28	15,95	27,25	3,96	5,16	10,600	250
3/4"	19,46	19,13	32,13	4,78	5,94	18,100	250
7/8"	22,71	22,30	37,06	5,56	6,76	29,400	100
1"	26,01	25,48	42,06	6,35	7,54	42,600	100
1 1/8"	29,29	28,68	46,91	7,14	8,33	58,500	50
1 1/4"	32,51	31,85	51,71	7,92	9,12	77,120	50
1 1/2"	38,96	38,20	61,44	9,53	10,72	132,000	50
1 3/4"	45,44	44,65	68,05	9,88	10,77	149,000	10
2"	51,79	51,00	74,57	10,72	10,85	180,000	10

Material

STAINLESS STEEL AISI 304 / AISI 316 Hardness: 345 - 420 Hv

CARBON STEEL Hardness: 372 - 458 Hv

Coatings:	plain oiled	black oxide	electro zinc plated white / yellow, baked
	hot dip galvanised	zinc-flake	mechanical zinc plated white / yellow